



FBHC

60 HELMET FOOTBALL CART

Features:

- Durable 1" Chrome plated steel tubing
- Holds up to 60 helmets
- 4 Swivel casters, 2 that lock
- Fits through standard doorways
- 61"L x 24"W x 65"H

Instructions:

Keep your team's helmets neatly organized and easy to transport with this Champion Sports Football Helmet Cart.

1. Start with the 20, 29 $\frac{1}{4}$ " shelf bars with push-button and 20, 29 $\frac{1}{4}$ " shelf bars with a hole for the push button. Join 1 each bar with push-button to 1 each bar with push hole. Repeat for all shelf bars to create 20 shelf bars. Figure 1
2. Assemble end uprights using U-shaped top bar and attaching two (2) end upright bars with pre-drilled holes on one side and two (2) end uprights with pre-drilled holes on the opposite side. Figure 2
3. Locate the 3, 20 $\frac{1}{2}$ " length end bars with pre-drilled holes and 2 each 20 $\frac{1}{2}$ " length end bars with pre-drilled holes and pre-drilled center hole. Assemble each horizontal end bar between the assembled upright bars with a U-shaped bar on the top. Attach using black plastic spacers and screws with locknuts. The horizontal end bars with the pre-drilled center holes will be attached to row two (2) and row four (4). DO NOT TIGHTEN SCREWS! Leave slightly loose to aide in further assembly. Repeat Step 4 for opposite end uprights. Refer to the above photo for how the end section will look once assembled. Figure 3
5. Attach a caster wheel to the bottom of assembled uprights. Each locking caster wheel will be attached to one upright and each regular caster wheels will be attached to opposite upright. Figure 4
6. Attach shelf bars by starting at the bottom of each upright and attaching four (4) shelf bars per row using black plastic spacers and screws with lock washers. DO NOT TIGHTEN THE SCREWS! Leave slightly loose until all bars are attached.
7. Attach center crossbar to rows two (2) and four (4) on each end pre-drilled center hole using wing nuts provided. Take note that it is easier to attach if all screws on shelf bars were left loose. Figure 5

Now that all parts are assembled go back and tighten all screws used in assembly. Be sure tightened and the helmet cart is sturdy.



Figure 1




Figure 2





Figure 3



PARTS:

- 2 U-shaped end top bars
- 8 End uprights with pre-drilled holes
- 20 (29 $\frac{1}{4}$ " Shelf bars with push buttons
- 20 (29 $\frac{1}{4}$ " shelf bars with hole for push buttons
- 4 (20 $\frac{1}{2}$ " End bars w/pre-drilled holes & center hole
- 6 (20 $\frac{1}{2}$ " End bars w/2 pre-drilled holes
- 1 Cross brace with 4 wing nuts
- 60 Screws w/lock washers
- 60 Black plastic end spacers
- 4 Wing Nuts
- 2 Caster wheels
- 2 Locking caster wheels

Figure 4




Figure 5

