

Features:

- 100 lb capacity
- Four pneumatic tires
- Heavy-duty steel construction
- Adjustment lever to paint either 2"W or 4"W lines
- Hinged lid to keep material dry

Parts:

- Ⓐ 1 Bucket/Frame Assembly
- Ⓑ 1 Handlebar
- Ⓒ 1 Adjustment Rod
- Ⓓ 1 Adjustment Handle
- Ⓔ 1 Adjustment Lever
- Ⓕ 1 Notched Plate
- Ⓖ 2 Hex Bolts M8 x 20mm
- Ⓗ 12 Washers M8
- Ⓘ 6 Locknuts M8
- ⓵ 1 Cotter Pin
- Ⓚ 2 Non-Drive Rear Wheels
- Ⓛ 2 Drive Front Wheels
- Ⓜ 4 Hex Bolts M8-35mm
- Ⓝ 2 Short Upper Bucket Braces
- Ⓞ 2 Long Lower Bucket Braces



Instructions:

Start your season off right with this heavy duty 100 lb dry line marker. It's among the most durable line markers on the market.

1. Attach the upper and lower bucket braces (Ⓝ and Ⓞ) to the bucket and frame assembly Ⓐ. Figure 2.
2. Attach the handlebar Ⓑ to the frame. Figure 1.
3. Connect the adjustment rod Ⓒ by sliding the end of the rod with the hole through the adjustment handle Ⓓ all the way through until the rod can be rotated down to position the end into the adjustment lever Ⓔ near the left front wheel. Figure 3.
4. Insert the end of the rod Ⓒ through the adjustment lever Ⓔ and secure in place with the cotter pin ⓵ provided. Figure 4.

